

DUCKHAMS HYPERGRADE PLUS 10W-40 API SL

PRODUCT DESCRIPTION

Duckhams Hypergrade Plus 10W-40 API SL is a semi synthetic engine oil formulated using conventional additive technology and high-quality virgin base oils to meet the requirements of existing vehicles and provide complete protection for modern passenger cars.

The multi-grade oil is suitable for year-round use. Formulated to control deposit formation and protect from rust, wear and corrosion, Duckhams Hypergrade Plus 10W-40 API SL offers complete protection from oil change to oil change. The low volatility oil reduces oil consumption, reducing running costs.



FEATURES AND BENEFITS

- Good anti-wear properties protect the engine and extend engine life.
- Good Rust and Corrosion protection extends engine life.
- Deposit control maintains engine cleanliness, maintaining engine performance through the oil drain interval.
- Suitable for year-round use
- Low Volatility reduces oil consumption, reducing top up and running costs.
- Original, distinctive, Duckhams green colour.

SPECIFICATIONS AND APPROVALS

Is Approved for use where the following specification is required;

API SL

TYPICAL PHYSICAL CHARACTERISTICS

Property	Unit	Typical Data
Viscosity Grade	-	10W-40
Colour	-	Green
Viscosity @ 100°C	cSt	15.0
Viscosity @ 40°C	cSt	103
Viscosity Index	-	152
CCS @ -30°C	cP	6,530
Flash Point (Closed Cup)	°C	250
Pour Point	°C	-36
Total Base Number	mgKOH/g	7.5
Density @ 15°C	Kg/L	0.8650

Typical physical characteristics are provided as indication of properties based on current production data only, and should not be construed as a specification. Acceptable variation may occur during the manufacturing process without affecting the performance of the lubricant. This data can change without notification. Current version of this data supersedes all previous versions.

HEALTH, SAFETY AND ENVIRONMENT

Based on available information this product is not expected to present a significant health and safety hazard when used in the recommended applications and in accordance with the recommendations in the Safety Data Sheet. Safety Data Sheet available on request through your sales agent, or from the internet. Avoid prolonged or repeated contact with engine oils. Wash skin thoroughly after contact.

Protect the environment. Dispose of product and packaging in accordance with local regulations.

STORAGE AND HANDLING

Packed lubricants should be stored under cover. Where outside storage of drums is unavoidable, they should be laid horizontal to avoid water ingress. Product should not be stored in direct sunlight or excessively high, or low, temperatures. Duckhams can provide professional advice on the storage of lubricants.
