

Duckhams Fleetol 40,50 CF**PRODUCT DESCRIPTION**

Duckhams Fleetol is a range of mono-grade diesel engine oils for automotive and commercial use. Formulated using updated additive technology and high-quality virgin base oils to meet older specifications and provide reliable protection for light trucks, vans and other vehicles operating under moderate conditions.

Duckhams Fleetol CF is mineral engine oil suitable for use in indirect injected diesel engines and other diesel engines, using a range of diesel fuels with higher sulphur content. It gives effective control of engine wear and piston deposits.



FEATURES AND BENEFITS

- Effective control of piston deposits maintains engine condition and performance.
- Reduces engine wear, extending engine operating life, maintaining engine performance and reducing total running costs
- Effective rust control maintains the condition and prolongs the life, of the engine.
- Compatible with yellow metal components.
- Suitable for use with higher sulphur diesel fuel.

SPECIFICATIONS AND APPROVALS

Meets or exceeds the required performance level for;

API CF

TYPICAL PHYSICAL CHARACTERISTICS

Property	Unit	Typical Data	Typical Data
Viscosity Grade	-	SAE 40	SAE 50
Viscosity @ 100°C	cSt	16.10	18.54
Viscosity @ 40°C	cSt	176.6	205.36
Viscosity Index	-	98	99
Flash Point (Closed Cup)	°C	248	252
Pour Point	°C	-9	-9
Total Base Number	mgKOH/g	9.2	9.2
Density @ 15°C	Kg/L	0.9030	0.9040
Product Code		5202P	5203P

Typical physical characteristics are provided as an indication of properties based on current production data only, and should not be construed as a specification. Acceptable variation may occur during the manufacturing process without affecting the performance of the lubricant. This data can change without notification. Current version of this data supersedes all previous versions.

HEALTH, SAFETY AND ENVIRONMENT

Based on available information this product is not expected to present a significant health and safety hazard when used in the recommended applications and in accordance with the recommendations in the Safety Data Sheet. Safety Data Sheet available on request through your sales agent, or from the internet. Avoid prolonged or repeated contact with engine oils. Wash skin thoroughly after contact.

Protect the environment. Dispose of product and packaging in accordance with local regulations.

STORAGE AND HANDLING

Packed lubricants should be stored under cover. Where outside storage of drums is unavoidable, they should be laid horizontal to avoid water ingress. Product should not be stored in direct sunlight or excessively high, or low, temperatures. Duckhams can provide professional advice on the storage of lubricants.
