

**DUCKHAMS Q 20W-50 SL****PRODUCT DESCRIPTION**

Duckhams Q was the first multigrade engine oil marketed in Europe. Duckhams Q 20W-50 SL is a mineral oil engine lubricant formulated using updated additive technology and high-quality virgin base oils to meet older specifications and provide reliable protection for modern passenger cars.

Duckhams Q 20W-50 SL is multigrade engine oil, suitable for year-round use, formulated to provide reliable anti-wear and corrosion protection. Deposit control maintains engine cleanliness, and low volatility formulation reduces oil consumption ensuring the correct level of protection throughout the oil drain interval.



---

**FEATURES AND BENEFITS**

- Good anti-wear properties protect the engine.
- Good Rust and Corrosion protection.
- Deposit control maintains engine cleanliness.
- Multigrade engine oil, suitable for year-round use.
- Low Volatility reduces oil consumption.
- Original, distinctive, Duckhams green colour.

---

**SPECIFICATIONS AND APPROVALS**

Meets or exceeds the required performance level for;

**API SL**

Can be used where the following specification is required:

**API CF/CF-4**

---



**TYPICAL PHYSICAL CHARACTERISTICS**

<b>Property</b>	<b>Unit</b>	<b>Typical Data</b>
Viscosity Grade	-	20W-50
Colour	-	Green
Viscosity @ 100°C	cSt	19.30
Viscosity @ 40°C	cSt	169.11
Viscosity Index	-	130
CCS @ -15°C	cP	6630
Flash Point (COC)	°C	238
Pour Point	°C	-24
Total Base Number	mgKOH/g	9.23
Density @ 15°C	Kg/L	0.8956

Typical physical characteristics are provided as an indication of properties based on current production data only, and should not be construed as a specification. Acceptable variation may occur during the manufacturing process without affecting the performance of the lubricant. This data can change without notification. Current version of this data supersedes all previous versions.

---

**HEALTH, SAFETY AND ENVIRONMENT**

Based on available information this product is not expected to present a significant health and safety hazard when used in the recommended applications and in accordance with the recommendations in the Safety Data Sheet. Safety Data Sheet available on request through your sales agent, or from the internet. Avoid prolonged or repeated contact with engine oils. Wash skin thoroughly after contact.

Protect the environment. Dispose of product and packaging in accordance with local regulations.

---

**STORAGE AND HANDLING**

Packed lubricants should be stored under cover. Where outside storage of drums is unavoidable, they should be laid horizontal to avoid water ingress. Product should not be stored in direct sunlight or excessively high, or low, temperatures. Duckhams can provide professional advice on the storage of lubricants.

---